

VMC Joystick

Joystick of the VMC control panel as stand-alone device



The **VMC Joystick** is a USB input device for systems with Microsoft Windows operating system. After connection, it is installed automatically with the standard driver already integrated in the operating system and facilitates the control of any applications.

In combination with **SMAVIA Viewing Client** or a **SeMSy® Workstation**, the VMC Joystick can be used for autonomous selection and display of the cameras of a recording system, independently of mouse or keyboard. The main function of the intuitive control of PTZ dome cameras can also be rounded off by freely configurable function keys for aperture, focus or zoom.

With its sophisticated ergonomics and high-quality optics, the **VMC Joystick** allows efficient and relaxed working.

Features

- Suitable for Microsoft Windows¹⁾ 7/8/10 systems
- Automatic installation with standard driver
- Control of any applications
- Intuitive PTZ camera control
- Compatible with SMAVIA Viewing Client
- Compatible with SeMSy® Video Management systems
- User-friendly 3-axis mechanism
- Pan, tilt, zoom with variable speed
- Supported protocols DCCP, Pelco D, Pelco
- Smooth and low-maintenance surface
- Ergonomic operation due to intelligent design
- Versatile use due to high-quality optics
- DIN EN 50130-4 compliant

Hardware

006324



VMC Joystick

Joystick module of the VMC control panel as stand-alone device,
1x USB 2.0 cable 2m

1) Microsoft and Windows are trademarks or registered trademarks of Microsoft Corporation headquartered in Redmond, Washington, USA

VMC Joystick

Joystick of the VMC control panel as stand-alone device

General	
Operating system	Microsoft Windows 7/8/10
Applications	Control of any applications supported
Camera control	
Applications	SMAVIA Viewing Client SeMSy® 5 Workstation SeMSy® III Workstation SeMSy® II Workstation
Supported recording systems	Dallmeier recording systems
Supported cameras	Dallmeier PTZ cameras with DCCP control protocol 3rd Party PTZ cameras with Pelco D or Pelco P control protocol
Interface	
Connections	1x USB 2.0 type B
Baud rate	2.4 – 57.6 kbps
Joystick	
Type	3 axes with function keys
Function	Pan, tilt, zoom with variable speed
Protocols supported	DCCP, Pelco D, Pelco P
Electrical data	
Power supply	5V DC (over USB)
Power consumption	Max. 2.5W
Mechanical Data	
Dimensions (W x H x D)	Approx. 138 x 128 x 224 mm (5.4" x 5.0" x 8.8")
Weight	Approx. 1.2kg (2.6 lb)
Color	Black
Environmental Conditions	
Temperature	+5°C to +35°C (41°F – 95°F)
Recommended temperature	+20°C to +25°C (68°F – 77°F)
Humidity	5 – 70% RH, non-condensing
Atmospheric load	Dust-free
Approvals and certifications	
Type	CE, FCC, RCM, DIN EN 50130-4 compliant

Dallmeier electronic GmbH & Co.KG | Bahnhofstr. 16, 93047 Regensburg, Germany | +49 941 8700-0 | dallmeier.com

All trademarks identified by * are registered trademarks of Dallmeier electronic GmbH & Co.KG.

Third-party trademarks are named for information purposes only. Dallmeier electronic respects the intellectual property of third parties and always attempts to ensure the complete identification of third-party trademarks and indication of the respective holder of rights. In case that protected rights are not indicated separately, this circumstance is no reason to assume that the respective trademark is unprotected.

Specifications subject to change without notice. Errors and misprints excepted. Pictures may differ from the actual product.



See more.