

VMC-2

Video Management Center for the Control of the SeMSy® Video Management System with Joystick, Touch Screen and Jog-Shuttle



The Video Management Center **VMC-2** is designed for the control of the SeMSy® Video Management System over a **SeMSy® Workstation**.

The **VMC-2** is made up of the components **VMC Joystick**, **VMC Touch** and **VMC Jog-Shuttle** in a modular and very flexible way. The individual components are **freely positionable** and therefore ideally suited for left- and right-handers. It is **also** possible to use the components independently of each other **as stand-alone devices**.

VMC Joystick

The joystick enables the security operator to conveniently control movable cameras. Pan, tilt and zoom movements can be performed intuitively. With just a single click on the joystick button, the camera automatically returns to its home position. If the mode is switched, the joystick can also be used as a mouse and thus allows simple menu control.

VMC Touch

The touch screen extends a workstation by a simple and convenient multi-touch control of the functions displayed on the monitor. The intuitive user interface allows the security operator to activate live streams in any viewer on the workstation and to precisely control PTZ cameras. Full control over the playback of recordings is supported, as is the definition and triggering of backups. In addition, an advanced snapshot function can be used for individual markings and comments directly in the image.

VMC Jog-Shuttle

The Jog-Shuttle is ideal for quickly finding specific frames in a video sequence. By rotating the central jog-dial, the security operator can easily move through individual frames. With the help of the surrounding shuttle ring, the scenes can then be played backwards or forwards at different speeds.

Features

- Compatible with SeMSy® systems
- Joystick for intuitive control of PTZ dome cameras
- Touch screen for easy operation of SeMSy® Maps
- Touch screen for easy operation of playback functions
- Jog-Shuttle for detailed evaluation of video sequences
- Smooth and low-maintenance surface
- Ergonomic operation due to intelligent design
- Flexible positioning of the individual components
- DIN EN 50130-4 compliant

Hardware

005683



VMC-2

Modular control panel consisting of VMC Joystick, VMC Jog-Shuttle, VMC Touch and Holder, including license DLD - SeMSy® VMC Touch Module for one SeMSy® Workstation

VMC-2

Video Management Center for the Control of the SeMSy® Video Management System with Joystick, Touch Screen and Jog-Shuttle

VMC Joystick	
Type	3 axes with function keys
Connections	1x USB 2.0 type B
Power supply	5V DC (over USB)
Power consumption	Max. 2.5W
Dimensions (W x H x D)	Approx. 138 x 128 x 224 mm (5.4" x 5.0" x 8.8")
Weight	Approx. 1.2 kg (2.6 lb)
Color	Black
Temperature	+5°C to +35°C (41°F to 95°F)
Humidity	5 – 70 % RH, non-condensing
Certificates	CE, FCC, RCM, DIN EN 50130-4

VMC Touch	
Type	Capacitive LCD touch screen
Size	38 cm diagonally (15.6")
Format and resolution	16:9 / 1920 x 1080
Brightness	220 cd/m ²
Number of touch points	10x multi touch
Diameter of touch points	> 6.5 mm
View angle	Up to 80° from any direction
Connections	1x VGA / 1x microHDMI / 1x microUSB / 1x Audio
Speaker	2x 1W
Power supply	5V DC (over microUSB)
Power consumption	Max. 2.5W
Dimensions (W x H x D)	Approx. 430 x 248 x 10 mm (17.0" x 9.7" x 0.4")
Weight	Approx. 1.4 kg
Color	Black
Temperature	+5°C to +35°C (41°F to 95°F)
Humidity	5 – 70 % RH, non-condensing
Certificates	CE, FCC, RCM

VMC Touch Holder	
Adjustment	Horizontal axis
Material	Aluminum
Dimensions (W x H x D)	Approx. 440 x 280 x 25 mm (17.3" x 11.0" x 1.0")
Weight	Approx. 3.1 kg (6.8 lb)
Color	Black/Silver

VMC Jog-Shuttle	
Type	Jog-dial with function keys
Connections	1x USB 2.0 type B
Power supply	5V DC (over USB)
Power consumption	Max. 2.5W
Dimensions (W x H x D)	Approx. 138 x 63 x 224 mm (5.4" x 2.5" x 8.8")
Weight	Approx. 1.1 kg
Color	Black
Temperature	+5°C to +35°C (41°F to 95°F)
Humidity	5 – 70 % RH, non-condensing
Certificates	CE, FCC, RCM, DIN EN 50130-4

Dallmeier electronic GmbH & Co.KG | Bahnhofstr. 16, 93047 Regensburg, Germany | +49 941 8700-0 | dallmeier.com

All trademarks identified by * are registered trademarks of Dallmeier electronic GmbH & Co.KG.

Third-party trademarks are named for information purposes only. Dallmeier electronic respects the intellectual property of third parties and always attempts to ensure the complete identification of third-party trademarks and indication of the respective holder of rights. In case that protected rights are not indicated separately, this circumstance is no reason to assume that the respective trademark is unprotected.

Specifications subject to change without notice. Errors and misprints excepted. Pictures may differ from the actual product.



See more.