

PoE Midspan 30W

Midspan power supply unit, 1× Ethernet, 10/100/1000Base-T, 802.3at, 802.3af, 30 W



Features

- IEEE 802.3at compliant
- IEEE 802.3af compatible
- Output power 30 W
- Supports 10/100/1000Base-T
- Automatic output adaptation
- Compact design

Specifications	
Number of ports	1
Data rate	10/100/1000 Mbps
Connectors	Shielded RJ-45, EIA 568A and 568B
LED indicators	AC Power (yellow) Channel Power (green)
PoE standards	IEEE 802.3at, IEEE802.3af
Power over Ethernet OUT	55 V DC, 30 W, pin 4/5 (+), pin 7/8 (-)
Voltage supply	115/230 V AC ±10%, 50/60 Hz
Dimensions (WxHxL)	53 mm x 33 mm x 140 mm (2.1" x 1.3" x 5.5")
Weight	200 g (0.44 lbs)
Operating temperature	-20°C to +40°C (-4°F to 104°F)
Relative humidity	0% – 90% RH, non-condensing
Approvals/Certifications	CE, FCC, UL/cUL, RoHS compliant

Accessories

004316



PoE Midspan 30W

Midspan power supply unit, 1× Ethernet port, 10/100/1000Base-T, 802.3at, 802.3af, 30 W